WD300

DR Soft label AM degausser



Audible and visual warninga

Two modes of use

Label detection function: Audible and optical alarm. Detects only soft labels, but does not degausse soft labels
Conventional use: sound and light warning, soft label degaussing



Degaussing & Use

Degaussing height: 5 ~ 13cm (depending on label direction)
Place the soft label in a valid range at the top of the panel
Sound and light warning, after the beep
Remove the label. Degaussing over



Note: If you need embedded desktop
Make a 21 x 17cm hole on the desktop

Synchronization function

The potentiometer can be adjusted to synchronize with other electronic devices to avoid phase interference
Frequency: 58Khz Input voltage: 110-230V



Product parameter

Appearance dimension	230x200x55mm	Degaussing Altitude	5~13cm (depending on label direction)
Perforation dimension	210x170mm	Frequency	58Khz
Outer box dimension	900x290x380mm	Input voltage	110-230V
Weight	2.1kg/10pcs/box (22kg)	Colour	Dark grey

Usage: ① embedded ② desktop

Scene use

One machine, two machines, one machine. - Two ways

Embedded

First, cut 21x17cm holes on the desktop and put in the degausser
Make it flush with the desktop for perfect invisibility

Desktop

Use directly on the desktop without opening holes
Can be moved at will, no need to fix